TOPEAGLE®

TBH-6000D

电脑假眼机

COMPUTERIZED IMITATION BUTTON HOLE MACHINE

[技术参数] TECHNICAL PARAMETERS

电子控制 Electronic Control	定针位 Needle Positioning	使用机针 EB750 10#-16# Needle EB750 10#-16#
电源 220V/50Hz Input 220V/50Hz	空气压力: 0.5Mpa Air Preassure: 0.5Mpa	缝制速度 1500~3500 针/分钟 Sewing Speed 1500~3500 Stitches/min
缝纫根数 1 Thread Number 1	加油方式:锭子油 Lubrication:Spindle	重量：毛重155公斤 净重120公斤 Weight：G.W：155KGS N.W：120KGS
切线器 Thread Trimmer	电机功率: 0.55~0.75Kw Motor Power: 0.55~0.75Kw	木箱整机包装：宽72CMx长122CMx116CM Package:72(W)x122(H)x116(L)/Wooden Case

[性能特点] CHARACTERISTICS

◎ 整机无油结构

◎ 电子控制锁眼针距大小、长度、间隔等

◎ 通过自动送布器，任意设定锁眼个数和锁眼之间的距离值

◎ 第三代自动送布装置

◎ 触摸屏操作面板

◎ 嵌入式一体化控制系统

◎ DD 马达（直接驱动）

◎ 数控上停针位

◎ 日本SMC气动元件

◎ 锁眼长度:15mm-25mm

◎ 最多连续缝制1-8个锁眼

◎ 可通过程序设定缝制的斜角和水平

◎ Oil-free structure of the whole machine

◎ Stitches size,length,distance and etc are electronically controlled

◎ Easy setup for numbers and distance of buttonholes due to the auto feeder

◎ Third generation automatic feeding device

◎ Touchable operation panel

◎ Embedded integrated control system

◎ DD motor（directly drive）

◎ Digital upper stop position

◎ SMC Japan pneumatic components

◎ Buttonhole length:15mm-25mm

◎ Buttonholes of each sewing cycle:1-8

◎ The angle and level of sewing can be set by program

西安鹰高进出口有限公司
TOPEAGLE INTERNATIONAL LTD.

地址：西安市高新区丈八二路31号逸翠尚府北区1栋4单元1201室
电话：+86-29-68723798
传真：+86-29-68723818
邮箱：sale@eagleco.cn
网址：www.topeaglesewing.com
邮编：710065

Add: 4-1201, Block 1, No.31 Zhangba Er Road, Xi 'an, China-710065
Tel : +86-29-68723798
Fax :+86-29-68723818
E-mail : sale@eagleco.cn
Web: www.topeaglesewing.com